

Safety Data Sheet

KERALASTIC rapido comp.A

Safety Data Sheet dated: 05/09/2022 - version 1



SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Mixture identification:

Trade name: KERALASTIC rapido comp.A

Trade code: 901025

UFI: Q1W5-102V-N00U-YWDS

1.2. Relevant identified uses of the substance or mixture and uses advised against

Recommended use: Epoxy-polyurethane adhesive

Uses advised against: Data not available

1.3. Details of the supplier of the safety data sheet

Company: MAPEI S.p.A. - Via Cafiero, 22 - 20158 Milano

Tel. +(39)02376731 (office hours) - Fax: +39-02-37673.214 - www.mapei.it

Responsible: sicurezza@mapei.it

1.4. Emergency telephone number

Centro antiveneni, Azienda ospedaliera "Antonio Cardarelli", III Servizio di anestesia e rianimazione, via Antonio Cardarelli 9, Napoli - Tel. 081 5453333

Centro antiveneni, Azienda ospedaliera universitaria Careggi, U.O. Tossicologia medica, via Largo Brambilla 3, Firenze - Tel. 055 7947819

Centro antiveneni, Centro nazionale d'informazione tossicologica, IRCCS Fondazione Salvatore Maugeri Clinica del lavoro e della riabilitazione, via Salvatore Maugeri 10, Pavia - Tel. 0382 24444

Centro antiveneni, Azienda ospedaliera Niguarda Ca' Granda, piazza Ospedale Maggiore 3, Milano - Tel. 02 66101029

Centro antiveneni, Azienda ospedaliera "Papa Giovanni XXIII", Tossicologia clinica, Dipartimento di farmacia clinica e farmacologia, piazza OMS 1, Bergamo - Tel. 800 883300

Centro antiveneni Policlinico "Umberto I", PRGM tossicologia d'urgenza, viale del Policlinico 155, Roma - Tel. 06 49978000

Centro antiveneni del Policlinico "Agostino Gemelli", Servizio di tossicologia clinica, largo Agostino Gemelli 8, Roma - Tel. 06 3054343

Centro antiveneni, Azienda ospedaliera universitaria Riuniti, viale Luigi Pinto 1, Foggia - Tel. 800 183459

Centro antiveneni, Ospedale pediatrico Bambino Gesù, Dipartimento emergenza e accettazione DEA, piazza Sant'Onofrio 4, Roma - Tel. 06 68593726

Centro antiveneni dell'Azienda ospedaliera universitaria integrata (AOUI) di Verona sede di Borgo Trento, piazzale Aristide Stefani, 1 - 37126 Verona - Tel. 800 011858

SECTION 2: Hazards identification



2.1. Classification of the substance or mixture

Regulation (EC) n. 1272/2008 (CLP)

Skin Irrit. 2

Causes skin irritation.

Eye Irrit. 2

Causes serious eye irritation.

Skin Sens. 1

May cause an allergic skin reaction.

Aquatic Chronic 3

Harmful to aquatic life with long lasting effects.

2

The concentration of isocyanate stated is the percentage by weight of the free monomer calculated with reference to the total weight of the mixture.

Adverse physicochemical, human health and environmental effects:

No other hazards

2.2. Label elements

Regulation (EC) n. 1272/2008 (CLP)

Pictograms and Signal Words



Warning

Hazard statements:

H315

Causes skin irritation.

H317

May cause an allergic skin reaction.

H319

Causes serious eye irritation.

H412 Harmful to aquatic life with long lasting effects.

Precautionary statements:

P261 Avoid breathing mist/vapours/spray.
P264 Wash hands thoroughly after handling.
P273 Avoid release to the environment.
P280 Wear protective gloves/clothing and eye/face protection.
P333+P313 If skin irritation or rash occurs: Get medical advice/attention.
P337+P313 If eye irritation persists: Get medical advice/attention.

Special Provisions:

EUH204 Contains isocyanates. May produce an allergic reaction.
EUH205 Contains epoxy constituents. May produce an allergic reaction.

Contains:

reaction product: bisphenol-A-
(epichlorhydrin); epoxy resin (number
average molecular weight <= 700)

Special provisions according to Annex XVII of REACH and subsequent amendments:

None.

2.3. Other hazards

No PBT, vPvB or endocrine disruptor substances
present in concentration >= 0.1%.

Other Hazards: No other hazards

This preparation contains low molecular weight epoxy resins. Cross sensitisation to other epoxies is possible. Avoid also exposure to spray mist and vapour.

SECTION 3: Composition/information on ingredients

3.1. Substances

Not Relevant

3.2. Mixtures

Mixture identification: KERALASTIC rapido comp.A

Hazardous components within the meaning of the CLP regulation and related classification:

Concentra tion (% w/w)	Name	Ident. Numb.	Classification	Registration Number	Properties :
≥5 - <10 %	reaction product: bisphenol-A- (epichlorhydrin); epoxy resin (number average molecular weight <= 700)	CAS:1675-54-3, 25068-38-6, 25085-99-8 EC:216-823-5 Index:603-073- 00-2	Skin Irrit. 2, H315 Skin Sens. 1, H317 Eye Irrit. 2, H319 Aquatic Chronic 2, H411 Specific Concentration Limits: C ≥ 5%: Skin Irrit. 2 H315 C ≥ 5%: Eye Irrit. 2 H319	01-2119456619-26	
≥2.5 - <5 %	o-xylene	CAS:1330-20-7 EC:215-535-7 Index:601-022- 00-9	Flam. Liq. 3, H226; Asp. Tox. 1, H304; STOT RE 2, H373; Acute Tox. 4, H312; Acute Tox. 4, H332; Skin Irrit. 2, H315; Eye Irrit. 2, H319; STOT SE 3, H335; Aquatic Chronic 3, H412	01-2119488216-32- XXXX	
≥0.25 - <0.49 %	4-nonylphenol, branched	CAS:84852-15-3 EC:284-325-5 Index:601-053- 00-8	Repr. 2, H361fd; Skin Corr. 1B, H314; Aquatic Acute 1, H400; Aquatic Chronic 1, H410; Acute Tox. 4, H302, M-Chronic:10, M- Acute:10	01-2119510715-45- XXXX	SVHC
≥0.1 - <0.25 %	nonylphenol	CAS:25154-52-3 EC:246-672-0 Index:601-053- 00-8	Repr. 2, H361; Skin Corr. 1B, H314; Aquatic Acute 1, H400; Aquatic Chronic 1, H410; Acute Tox. 4, H302		SVHC

SECTION 4: First aid measures

4.1. Description of first aid measures

In case of skin contact:

Immediately take off all contaminated clothing.

Areas of the body that have - or are only even suspected of having - come into contact with the product must be rinsed immediately with plenty of running water and possibly with soap.

Wash thoroughly the body (shower or bath).

Remove contaminated clothing immediately and dispose of safely.

After contact with skin, wash immediately with soap and plenty of water.

In case of eyes contact:

After contact with the eyes, rinse with water with the eyelids open for a sufficient length of time, then consult an ophthalmologist immediately.

Protect uninjured eye.

In case of Ingestion:

Do not induce vomiting, get medical attention showing the SDS and the hazard label.

In case of Inhalation:

Remove casualty to fresh air and keep warm and at rest.

4.2. Most important symptoms and effects, both acute and delayed

Eye irritation

Eye damages

Skin Irritation

Erythema

4.3. Indication of any immediate medical attention and special treatment needed

In case of accident or unwellness, seek medical advice immediately (show directions for use or safety data sheet if possible).

Treatment:

(see paragraph 4.1)

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media:

Water.

Carbon dioxide (CO₂).

Extinguishing media which must not be used for safety reasons:

None in particular.

5.2. Special hazards arising from the substance or mixture

Do not inhale explosion and combustion gases.

5.3. Advice for firefighters

Use suitable breathing apparatus.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Wear personal protection equipment.

Remove persons to safety.

6.2. Environmental precautions

Do not allow to enter into soil/subsoil. Do not allow to enter into surface water or drains.

Limit leakages with earth or sand.

6.3. Methods and material for containment and cleaning up

Suitable material for taking up: absorbing material, organic, sand

Retain contaminated washing water and dispose it.

6.4. Reference to other sections

See also section 8 and 13

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Avoid contact with skin and eyes, inhalation of vapours and mists.

Don't use empty container before they have been cleaned.

Before making transfer operations, assure that there aren't any incompatible material residuals in the containers.

Contaminated clothing should be changed before entering eating areas.

Do not eat or drink while working.

See also section 8 for recommended protective equipment.

7.2. Conditions for safe storage, including any incompatibilities

Keep away from food, drink and feed.

Incompatible materials:

None in particular.

Instructions as regards storage premises:

Adequately ventilated premises.

7.3. Specific end use(s)

Recommendation(s)

None in particular

Industrial sector specific solutions:

None in particular

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

List of components with OEL value

	OEL Type	Country	Ceiling	Long Term mg/m3	Long Term ppm	Short Term mg/m3	Short Term ppm	Behaviour	Note	
o-xylene CAS: 1330-20-7	National	SWEDEN		221	50	442	100		SWEDEN, Short term value, 15 minutes average value	
	National	FINLAND		220	50	440	100		FINLAND, hud	
	National	NORWAY		108	25				NORWAY, H	
	EU			221	50	442	100		Skin	
	National	NORWAY		109	25	218	50			
	ACGIH				100		150		A4, BEI - URT and eye irr, CNS impair	
	DFG	GERMANY	C			880	200			
	ACGIH				100		150		A4 - Not Classifiable as a Human Carcinogen; CNS impairment; eye and upper respiratory tract irritation	
	National	SWEDEN			221	50				
	National	FRANCE			221	50	442	100		
	National	SPAIN			221	50	442	100		
	National	GREECE			435	100	650	150		
	National	DENMARK			109	25				
	National	FINLAND			220	50	440	100		
	National	GERMANY			440	100				
	National	PORTUGAL			221	50	442	100		
	National	BELGIUM			221	50	442	100		
	NDS	POLAND			100					
	NDSch	POLAND					200			
	CHE	SWITZERLAND					870	200		
	NDS	NETHERLANDS			210		442			
	National	CZECH REPUBLIC			200					
	National	HUNGARY			221		442			
	Malaysi a OEL	MALAYSIA			434	100				
	National	ESTONIA			200	50	450	100		
	National	LATVIA			221	50	442	100		
	National	CZECH REPUBLIC	C				400			
	National	SLOVAKIA	C				442			
	National	SLOVAKIA			221	50				
	National	SLOVENIA			221	50	442	100		
National	UNITED KINGDOM			220	50	441	100			
National	BULGARIA			221.0	50	442	100			
National	ROMANIA			221	50	442	100			

TUR	TURKEY	221	50	442	100		
National	LITHUANIA	221	50	442	100		
National	CROATIA	221	50	442	100		
EU		221	50	442	100	Indicative	Possibility of significant uptake through the skin (pure)

Biological Exposure Index

	Value	UoM	Medium	Biological Indicator	Sampling Period
o-xylene CAS: 1330-20-7	1,5	GGCREAT	Urine	Methyl uric Acid	End of turn

Predicted No Effect Concentration (PNEC) values

	PNEC Limit	Exposure Route	Exposure Frequency	Remark
o-xylene CAS: 1330-20-7	0.327 mg/l	Fresh Water		
	0.327 mg/l	Marine water		
	12.46 mg/kg	Freshwater sediments		
	12.46 mg/kg	Marine water sediments		
	2.31 mg/kg	Soil		
	6.58 mg/l	Microorganisms in sewage treatments		
4-nonylphenol, branched CAS: 84852-15-3	0.32 mg/l	Intermittent release		
	0.000614 mg/l	Fresh Water		
	0.000527 mg/l	Marine water		
	4.62 mg/kg	Freshwater sediments		
	1.23 mg/kg	Marine water sediments		

Derived No Effect Level. (DNEL)

	Worker Industrial	Worker Professional	Consumer	Exposure Route	Exposure Frequency	Remark
o-xylene CAS: 1330-20-7	289 mg/m3		174 mg/m3	Human Inhalation	Short Term, local effects	
	289 mg/m3		174 mg/m3	Human Inhalation	Short Term, systemic effects	
	180 mg/kg		108 mg/kg	Human Dermal	Long Term, systemic effects	
	77 mg/m3		14.8 mg/m3	Human Inhalation	Long Term, systemic effects	
			1.6 mg/kg	Human Oral	Long Term, systemic effects	
4-nonylphenol, branched CAS: 84852-15-3	0.5 mg/m3		0.4 mg/m3	Human Inhalation	Long Term, systemic effects	
	1 mg/m3		0.8 mg/m3	Human Inhalation	Short Term, systemic effects	
	7.5 mg/kg		3.8 mg/kg	Human Dermal	Long Term, systemic effects	
	15 mg/kg		7.6 mg/kg	Human Dermal	Short Term, systemic effects	

0.08 mg/kg	Human Oral	Long Term, systemic effects
0.4 mg/kg	Human Oral	Short Term, systemic effects

8.2. Exposure controls

Eye protection:

Use close fitting safety goggles, don't use eye lens.

Protection for skin:

Use clothing that provides comprehensive protection to the skin, e.g. cotton, rubber, PVC or viton.

Protection for hands:

Suitable materials for safety gloves; EN ISO 374:

Polychloroprene - CR: thickness $\geq 0,5\text{mm}$; breakthrough time $\geq 480\text{min}$.

Nitrile rubber - NBR: thickness $\geq 0,35\text{mm}$; breakthrough time $\geq 480\text{min}$.

Butyl rubber - IIR: thickness $\geq 0,5\text{mm}$; breakthrough time $\geq 480\text{min}$.

Fluorinated rubber - FKM: thickness $\geq 0,4\text{mm}$; breakthrough time $\geq 480\text{min}$.

Neoprene gloves are suggested (0,5 mm) not recommended gloves: not waterproof gloves

Respiratory protection:

Personal Protective Equipment should comply with relevant CE standards (as EN ISO 374 for gloves and EN ISO 166 for goggles), correctly maintained and stored. Consult the supplier to check the suitability of equipment against specific chemicals and for user information.

Respiratory protection must be used where exposure levels exceed workplace exposure limits. Refer to appropriate EN standards, like EN 136, 140, 143, 149, 14387 for information on selection and use of appropriate respiratory protection equipment.

In case of insufficient ventilation use mask with ABEKP filters (EN 14387).

Hygienic and Technical measures

Not available

Appropriate engineering controls:

Not available

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state: Liquid

Appearance: paste

Color: various

Odour: Characteristic

Odour threshold: Not available

Melting point / freezing point: Not available

Initial boiling point and boiling range: Not available

Flammability: N.A.

Upper/lower flammability or explosive limits: Not available

Flash point: Not available

Auto-ignition temperature: Not available

Decomposition temperature: Not available

pH: Not available

Viscosity: Not available

Kinematic viscosity: Not available

Solubility in water: Insoluble

Solubility in oil: soluble

Partition coefficient (n-octanol/water): Not available

Vapour pressure: Not available

Relative density: Not available

Vapour density: ==

Particle characteristics:

Particle size: Not available

9.2. Other information

Miscibility: Not available

Conductivity: Not available

Explosive properties: ==

No other relevant information

SECTION 10: Stability and reactivity

10.1. Reactivity

Stable under normal conditions

10.2. Chemical stability

Stable under normal conditions

10.3. Possibility of hazardous reactions

None.

10.4. Conditions to avoid

Stable under normal conditions.

10.5. Incompatible materials

None in particular.

10.6. Hazardous decomposition products

None.

SECTION 11: Toxicological information

11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008

Toxicological information of the mixture:

a) acute toxicity	Not classified
	Based on available data, the classification criteria are not met
b) skin corrosion/irritation	The product is classified: Skin Irrit. 2(H315)
c) serious eye damage/irritation	The product is classified: Eye Irrit. 2(H319)
d) respiratory or skin sensitisation	The product is classified: Skin Sens. 1(H317)
e) germ cell mutagenicity	Not classified
	Based on available data, the classification criteria are not met
f) carcinogenicity	Not classified
	Based on available data, the classification criteria are not met
g) reproductive toxicity	Not classified
	Based on available data, the classification criteria are not met
h) STOT-single exposure	Not classified
	Based on available data, the classification criteria are not met
i) STOT-repeated exposure	Not classified
	Based on available data, the classification criteria are not met
j) aspiration hazard	Not classified
	Based on available data, the classification criteria are not met

Toxicological information on main components of the mixture:

reaction product: bisphenol-A- (epichlorhydrin); epoxy resin (number average molecular weight <= 700)	a) acute toxicity	LD50 Skin Rabbit = 20 mg/kg
		LD50 Oral Rat = 11300 µL/kg
		LD50 Skin Rabbit = 20000 mg/kg
o-xylene	a) acute toxicity	LD50 Oral Rat > 2000 mg/kg
		LC50 Inhalation Vapour Rat = 11 mg/l 4h
		LD50 Skin Rabbit = 3200 mg/kg
		LD50 Skin Rabbit > 4350 mg/kg
		LC50 Inhalation Rat = 29.08 mg/l 4h
		LD50 Oral Rat = 3500 mg/kg
	e) germ cell mutagenicity	NOAEL Inhalation Rat > 2000 ppm
f) carcinogenicity	NOAEL Oral Rat = 500 mg/kg	
	NOAEL Oral Rat = 1000 mg/kg	
g) reproductive toxicity	NOAEL Inhalation Rat = 500 ppm	
4-nonylphenol, branched	a) acute toxicity	LD50 Oral Rat = 1246 mg/kg
		LD50 Skin Rabbit = 2031 mg/kg
	b) skin corrosion/irritation	Skin Irritant Rabbit Negative

d) respiratory or skin sensitisation Skin Sensitization Rat Negative

nonylphenol a) acute toxicity LD50 Skin Rabbit = 2031 mg/kg
LD50 Oral Rat = 580 mg/kg

11.2 Information on other hazards

Endocrine disrupting properties:

No endocrine disruptor substances present in concentration $\geq 0.1\%$

SECTION 12: Ecological information

12.1. Toxicity

Adopt good working practices, so that the product is not released into the environment.

Eco-Toxicological Information:

Harmful to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

List of Eco-Toxicological properties of the product

The product is classified: Aquatic Chronic 3(H412)

List of components with eco-toxicological properties

Component	Ident. Numb.	Ecotox Infos
o-xylene	CAS: 1330-20-7 - EINECS: 215-535-7 - INDEX: 601-022-00-9	a) Aquatic acute toxicity : EC50 Daphnia = 165 mg/L 48 a) Aquatic acute toxicity : LC50 Fish > 2 mg/L 96 a) Aquatic acute toxicity : EC50 Algae = 2.2 mg/L 72 c) Bacteria toxicity : EC50 = 96 mg/L 24 b) Aquatic chronic toxicity : NOEC Fish > 1.3 mg/L b) Aquatic chronic toxicity : NOEC Daphnia = 1.57 mg/L a) Aquatic acute toxicity : LC50 Fish Pimephales promelas = 13.4 mg/L 96h EPA a) Aquatic acute toxicity : LC50 Fish Oncorhynchus mykiss 2.661 mg/L 96h EPA a) Aquatic acute toxicity : LC50 Fish Oncorhynchus mykiss 13.5 mg/L 96h IUCLID a) Aquatic acute toxicity : LC50 Fish Lepomis macrochirus 13.1 mg/L 96h EPA a) Aquatic acute toxicity : LC50 Fish Lepomis macrochirus = 19 mg/L 96h EPA a) Aquatic acute toxicity : LC50 Fish Lepomis macrochirus 7.711 mg/L 96h EPA a) Aquatic acute toxicity : LC50 Fish Pimephales promelas 23.53 mg/L 96h EPA a) Aquatic acute toxicity : LC50 Fish Cyprinus carpio = 780 mg/L 96h EPA a) Aquatic acute toxicity : LC50 Fish Cyprinus carpio > 780 mg/L 96h IUCLID a) Aquatic acute toxicity : LC50 Fish Poecilia reticulata 30.26 mg/L 96h EPA a) Aquatic acute toxicity : EC50 Daphnia water flea = 3.82 mg/L 48h a) Aquatic acute toxicity : LC50 Daphnia Gammarus lacustris = 0.6 mg/L 48h
4-nonylphenol, branched	CAS: 84852-15-3 - EINECS: 284-325-5 - INDEX: 601-053-00-8	a) Aquatic acute toxicity : LC50 Fish Pimephales promelas = 0.135 mg/L 96h IUCLID a) Aquatic acute toxicity : LC50 Fish Lepomis macrochirus = 0.1351 mg/L 96h EPA a) Aquatic acute toxicity : EC50 Daphnia Daphnia magna = 0.14 mg/L 48h IUCLID a) Aquatic acute toxicity : EC50 Algae Pseudokirchneriella subcapitata 0.36 mg/L 96h EPA

a) Aquatic acute toxicity : EC50 Algae Pseudokirchneriella subcapitata 0.16 mg/L 72h EPA

a) Aquatic acute toxicity : EC50 Algae Desmodesmus subspicatus = 1.3 mg/L 72h IUCLID

nonylphenol

CAS: 25154-52-3 - EINECS: 246-672-0 - INDEX: 601-053-00-8

a) Aquatic acute toxicity : LC50 Fish Pimephales promelas = 0.135 mg/L 96h

a) Aquatic acute toxicity : EC50 Daphnia Daphnia magna = 0.14 mg/L 48h IUCLID

a) Aquatic acute toxicity : EC50 Daphnia Daphnia magna 0.17 mg/L 48h EPA

a) Aquatic acute toxicity : EC50 Daphnia Daphnia magna 0.0874 mg/L 48h EPA

a) Aquatic acute toxicity : EC50 Algae Pseudokirchneriella subcapitata = 0.41 mg/L 96h IUCLID

a) Aquatic acute toxicity : EC50 Algae Desmodesmus subspicatus = 1.3 mg/L 72h IUCLID

12.2. Persistence and degradability

N.A.

12.3. Bioaccumulative potential

Component	Bioaccumulation	Test	Duration	Value
4-nonylphenol, branched	Not bioaccumulative	BCF - Bioconcentration factor	28 d	740

12.4. Mobility in soil

N.A.

12.5. Results of PBT and vPvB assessment

No PBT, vPvB or endocrine disruptor substances present in concentration $\geq 0.1\%$.

12.6 Endocrine disrupting properties

No endocrine disruptor substances present in concentration $\geq 0.1\%$

12.7 Other adverse effects

Not available

SECTION 13: Disposal considerations

13.1. Waste treatment methods

The generation of waste should be avoided or minimized wherever possible. Recover if possible.

A waste code (EWC) according to European List of Waste (LoW) cannot be specified, due to dependence on the usage. Contact and send to an authorized waste disposal service.

Methods of disposal:

Disposal of this product, solutions, packaging and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements.

Dispose of surplus and nonrecyclable products via a licensed waste disposal contractor.

Do not dispose of waste into sewers.

Hazardous waste: Yes

Disposal considerations:

Do not allow to enter drains or watercourses.

Dispose of product according to all federal, state and local applicable regulations.

If this product is mixed with other wastes, the original waste product code may no longer apply and the appropriate code should be assigned.

Dispose of containers contaminated by the product in accordance with local or national legal provisions. For further information, contact your local waste authority.

Special precautions:

This material and its container must be disposed of in a safe way. Care should be taken when handling untreated empty containers.

Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers.

Empty containers or liners may retain some product residues. Do not re-use empty containers.

SECTION 14: Transport information

Not classified as dangerous in the meaning of transport regulations.

14.1. UN number or ID number

Not Applicable

14.2. UN proper shipping name

Not Applicable

14.3. Transport hazard class(es)

Not Applicable

14.4. Packing group

Not Applicable

14.5. Environmental hazards

Not Applicable

14.6. Special precautions for user

Not Applicable

Road and Rail (ADR-RID) :

Not Applicable

Air (IATA) :

Not Applicable

Sea (IMDG) :

Not Applicable

14.7. Maritime transport in bulk according to IMO instruments

Not Applicable

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

VOC (2004/42/EC) : N.A. g/l

Dir. 98/24/EC (Risks related to chemical agents at work)

Dir. 2000/39/EC (Occupational exposure limit values)

Regulation (EC) n. 1907/2006 (REACH)

Regulation (EU) n. 2020/878

Regulation (EC) n. 1272/2008 (CLP)

Regulation (EC) n. 790/2009 (ATP 1 CLP) and (EU) n. 758/2013

Regulation (EU) n. 286/2011 (ATP 2 CLP)

Regulation (EU) n. 618/2012 (ATP 3 CLP)

Regulation (EU) n. 487/2013 (ATP 4 CLP)

Regulation (EU) n. 944/2013 (ATP 5 CLP)

Regulation (EU) n. 605/2014 (ATP 6 CLP)

Regulation (EU) n. 2015/1221 (ATP 7 CLP)

Regulation (EU) n. 2016/918 (ATP 8 CLP)

Regulation (EU) n. 2016/1179 (ATP 9 CLP)

Regulation (EU) n. 2017/776 (ATP 10 CLP)

Regulation (EU) n. 2018/669 (ATP 11 CLP)

Regulation (EU) n. 2019/521 (ATP 12 CLP)

Regulation (EU) n. 2018/1480 (ATP 13 CLP)

Regulation (EU) n. 2020/217 (ATP 14 CLP)

Regulation (EU) n. 2020/1182 (ATP 15 CLP)

Provisions related to directive EU 2012/18 (Seveso III):

None

Restrictions related to the product or the substances contained according to Annex XVII Regulation (EC) 1907/2006 (REACH) and subsequent modifications:

Restrictions related to the product: 3

Restrictions related to the substances contained: 40, 46, 75

SVHC Substances:

Substances in candidate list (Art. 59 Reg. 1907/2006, REACH):

Component	Ident. Numb.	Quantity	Properties:
4-nonylphenol, branched	CAS: 84852-15-3	>=0.25 - <0.49 %	SVHC
	EINECS: 284-325-5		
	Index: 601-053-00-8		

German Water Hazard Class (WGK)

Class 2: hazardous for water.

15.2. Chemical safety assessment

No Chemical Safety Assessment has been carried out for the mixture.

SECTION 16: Other information

Code	Description
H226	Flammable liquid and vapour.
H302	Harmful if swallowed.
H304	May be fatal if swallowed and enters airways.
H312	Harmful in contact with skin.
H314	Causes severe skin burns and eye damage.
H315	Causes skin irritation.
H317	May cause an allergic skin reaction.
H319	Causes serious eye irritation.
H332	Harmful if inhaled.
H335	May cause respiratory irritation.
H361	Suspected of damaging fertility or the unborn child.
H361fd	Suspected of damaging fertility. Suspected of damaging the unborn child.
H373	May cause damage to organs through prolonged or repeated exposure.
H400	Very toxic to aquatic life.
H410	Very toxic to aquatic life with long lasting effects.
H411	Toxic to aquatic life with long lasting effects.
H412	Harmful to aquatic life with long lasting effects.

Code	Hazard class and hazard category	Description
2.6/3	Flam. Liq. 3	Flammable liquid, Category 3
3.1/4/Dermal	Acute Tox. 4	Acute toxicity (dermal), Category 4
3.1/4/Inhal	Acute Tox. 4	Acute toxicity (inhalation), Category 4
3.1/4/Oral	Acute Tox. 4	Acute toxicity (oral), Category 4
3.10/1	Asp. Tox. 1	Aspiration hazard, Category 1
3.2/1B	Skin Corr. 1B	Skin corrosion, Category 1B
3.2/2	Skin Irrit. 2	Skin irritation, Category 2
3.3/2	Eye Irrit. 2	Eye irritation, Category 2
3.4.2/1	Skin Sens. 1	Skin Sensitisation, Category 1
3.7/2	Repr. 2	Reproductive toxicity, Category 2
3.8/3	STOT SE 3	Specific target organ toxicity — single exposure, Category 3
3.9/2	STOT RE 2	Specific target organ toxicity — repeated exposure, Category 2
4.1/A1	Aquatic Acute 1	Acute aquatic hazard, category 1
4.1/C1	Aquatic Chronic 1	Chronic (long term) aquatic hazard, category 1
4.1/C2	Aquatic Chronic 2	Chronic (long term) aquatic hazard, category 2
4.1/C3	Aquatic Chronic 3	Chronic (long term) aquatic hazard, category 3

Classification and procedure used to derive the classification for mixtures according to Regulation (EC) 1272/2008 [CLP]:

Classification according to Regulation (EC) Nr. 1272/2008	Classification procedure
3.2/2	Calculation method
3.3/2	Calculation method
3.4.2/1	Calculation method
4.1/C3	Calculation method

If appropriate, specific provisions in relation to possible training for workers are mentioned in section 2. Any training related to safety in the

workplace must in any case refer to a risk assessment that must be carried out by a company safety officer taking into account the specific operating and environmental conditions in which the products are used.

This document was prepared by a competent person who has received appropriate training.

Main bibliographic sources:

ECDIN - Environmental Chemicals Data and Information Network - Joint Research Centre, Commission of the European Communities

SAX's DANGEROUS PROPERTIES OF INDUSTRIAL MATERIALS - Eight Edition - Van Nostrand Reinold

The information contained herein is based on our state of knowledge at the above-specified date. It refers solely to the product indicated and constitutes no guarantee of particular quality.

It is the duty of the user to ensure that this information is appropriate and complete with respect to the specific use intended.

This SDS cancels and replaces any preceding release.

Legend to abbreviations and acronyms used in the safety data sheet:

ACGIH: American Conference of Governmental Industrial Hygienists

ADR: European Agreement concerning the International Carriage of Dangerous Goods by Road.

AND: European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways

ATE: Acute Toxicity Estimate

ATEmix: Acute toxicity Estimate (Mixtures)

BCF: Biological Concentration Factor

BEI: Biological Exposure Index

BOD: Biochemical Oxygen Demand

CAS: Chemical Abstracts Service (division of the American Chemical Society).

CAV: Poison Center

CE: European Community

CLP: Classification, Labeling, Packaging.

CMR: Carcinogenic, Mutagenic and Reprotoxic

COD: Chemical Oxygen Demand

COV: Volatile Organic Compound

CSA: Chemical Safety Assessment

CSR: Chemical Safety Report

DMEL: Derived Minimal Effect Level

DNEL: Derived No Effect Level.

DPD: Dangerous Preparations Directive

DSD: Dangerous Substances Directive

EC50: Half Maximal Effective Concentration

ECHA: European Chemicals Agency

EINECS: European Inventory of Existing Commercial Chemical Substances.

ES: Exposure Scenario

GefStoffVO: Ordinance on Hazardous Substances, Germany.

GHS: Globally Harmonized System of Classification and Labeling of Chemicals.

IARC: International Agency for Research on Cancer

IATA: International Air Transport Association.

IATA-DGR: Dangerous Goods Regulation by the "International Air Transport Association" (IATA).

IC50: half maximal inhibitory concentration

ICAO: International Civil Aviation Organization.

ICAO-TI: Technical Instructions by the "International Civil Aviation Organization" (ICAO).

IMDG: International Maritime Code for Dangerous Goods.

INCI: International Nomenclature of Cosmetic Ingredients.

IRCCS: Scientific Institute for Research, Hospitalization and Health Care

KAFH: KAFH

KSt: Explosion coefficient.

LC50: Lethal concentration, for 50 percent of test population.

LD50: Lethal dose, for 50 percent of test population.

LDLo: Leathal Dose Low

N.A.: Not Applicable

N/A: Not Applicable

N/D: Not defined/ Not available

NA: Not available

NIOSH: National Institute for Occupational Safety and Health

NOAEL: No Observed Adverse Effect Level

OSHA: Occupational Safety and Health Administration.

PBT: Persistent, Bioaccumulative and Toxic

PGK: Packaging Instruction

PNEC: Predicted No Effect Concentration.

PSG: Passengers

RID: Regulation Concerning the International Transport of Dangerous Goods by Rail.

STEL: Short Term Exposure limit.

STOT: Specific Target Organ Toxicity.

TLV: Threshold Limiting Value.

TWATLV: Threshold Limit Value for the Time Weighted Average 8 hour day. (ACGIH Standard).

vPvB: Very Persistent, Very Bioaccumulative.

WGK: German Water Hazard Class.